

VED03 J Series

Proportional Directional Control Valves with Feedback and Integrated Digital Electronics

DESCRIPTION

VED03 J series Proportional valves are Direct Operated with Integrated Digital Electronics and use LVDT spool position feedback.

VED03JL style uses a compact box and M12- 5 Pin connection and also offers Analog, IO-Link and CANopen input interfaces.
See pages 3 - 5 for more details.




VED03MJ style uses the industry standard common 7 Pin connection and Analog inputs.
See pages 6 - 9 for more details.

VED03JH style provides for a variety of Fieldbus communication types.
See pages 10 - 14 for more details.


For all other performance data and accessories.
See pages 15 - 18

PERFORMANCE (Mineral oil with viscosity of 36 cSt at 50°C and p = 140 bar)

Max operating pressure: P - A - B ports T port	PSI (bar)	5000 (350) 3000 (201)
Nominal flow with Δp 10 bar P-T	l/min	1 - 4 - 12 - 18 - 30
Response times	see page 17	
Hysteresis	% of Q max	< 0.2%
Repeatability	% of Q max	< 0.2%
Threshold		< 0.1%
Valve reproducibility		≤ 5%
Electrical characteristics	see data under each style	
Ambient temperature range	°F (°C)	-4 / 140 (-20 / +60)
Fluid temperature range	°F (°C)	-4 / 176 (-20 / +80)
Fluid viscosity range	cSt	10 - 400
Fluid contamination degree	according to ISO 4406:1999 class 18/16/13	
Recommended viscosity	cSt	25
Mass: Single solenoid valve Double solenoid valve	lbs (kg)	4.85 (2.2) 5.95 (2.7)




**SUBPLATE MOUNTING NFPA D03
ISO 4401-03**

VED03 J Series

OPERATING PRINCIPLE


- The VED03 J valves are proportional directional valves, direct operated, with closed loop position control. The mounting interface is in compliance with ISO 4401 standards.
- The valve opening and hence flow rate can be modulated continuously in proportion to the reference signal. Transducer and digital card allow a fine control of the spool position, reducing both hysteresis and response times and optimizing the valve performance.
- The valves are available with different types of electronics, with analogue or fieldbus interfaces.
- The fail safe function is available for spools type Z.
- Valves are easy to install. The driver manages digital settings directly.

HYDRAULIC SYMBOLS (typical)


VED03*-3AC



VED03*-3FC



VED03*-3ZC




VED03 J Series

IDENTIFICATION CODE: Compact Electronics

VED03JL - - - - **K12** - _____ DESIGN LETTER

Proportional D03 Direct Operated Directional Control with Digital On-Board and Compact Box

Low Profile Connection Box with M12 A 5 Pin (Male)



SEALS	
CODE	DESCRIPTION
A	BUNA (STD)
G	VITON

NOMINAL CONTROLLED FLOW with ΔP 10 Bar P-T	
CODE	FLOW RATE
01	1 l/min
04	4 l/min
12	12 l/min
18	18 l/min (AC spool only)
30	30 l/min
30/15	30 (P-A) / 15 (P-B) l/min

CONTROL INTERFACE	
CODE	DESCRIPTION
E0	Analog Voltage (±10V)
E1	Analog Current (4-20mA)
IOL	IO-Link Interface
CA	CANopen Interface

SPOOLS				
NAME	SYMBOLS	DESCRIPTION	APPLICATION	FUNCTION MATCHING
AC		METER IN / METER OUT	MOTION CONTROL	3, 5
FC				
ZC				3
ZCF		METER IN / METER OUT WITH FAIL SAFE		10

Note: Function Code 5 valve only available with solenoid supplied on B port end. (P-A / B-T)



TYPICAL ORDERING CODE:
VSD03JL-3ZC-30-A-IOLK12.*

VED03 J Series
VED03JL - COMPACT ELECTRONICS



In versions 'IOL' and 'CA' pin 3 and pin 5 are galvanic isolated up to 100 V to avoid earth loops.
 In IO-Link networks, the length of the connecting cable is limited to 20 meters.

VED03JL Electrical Characteristics



Command signal: voltage (E0) current (E1)	V DC mA	±10 (Impedance Ri = 11 kOhm) 4 - 20 (Impedance Ri = 58 Ohm)
Monitor signal: voltage (E0) current (E1)	V DC mA	0 - 5 (Impedance Ro > 1 kOhm) 4 - 20 (Impedance Ro = 500 Ohm)
IO-Link communication (IOL): Data rate	kBaud	IO-Link Port Class B 230.4
Can Open communication (CA): Data rate	kbit	10 - 1000
Data register (IOL and CA versions only)		Solenoid voltage supply, solenoid faults (short circuit, bad config, internal), box temperature, switch-on time, vibrations
Connection		5-pin M12 code A (IEC 61076-2-101)

Pin tables
'E0' connection





Pin	Values	Function
2	24V DC	Supply voltage (solenoid and logic)
5	0V	
1	± 10V	Command
3	0V	Command reference
4	0 - 5V	Monitor (0V reference: pin 5)

'E1' connection



Pin	Values	Function
2	24V DC	Supply voltage (solenoid and logic)
5	0V	
1	4 - 20 mA	Command
3	0V	Command reference
4	4 - 20 mA	Monitor (0V reference: pin 5)

'IOL' connection





Pin	Values	Function
2	2L+ 24V DC	Supply of the power stage
5	2L- 0V (GND)	Internal galvanic isolation from PIN 3
1	1L+ +24V DC	IO-Link supply voltage
3	1L- 0V (GND)	
4	C/Q	IO-Link Communication

'CA' connection



Pin	Values	Function
1	CAN_SH	Shield
2	24V DC	Supply voltage
3	0V (GND)	
4	CAN H	Bus line (high)
5	CAN_L	Bus line (low)

VED03 J Series
VED03JL - OVERALL AND MOUNTING DIMENSIONS

Dimensions inch (mm)

VED03JL-3 K12**

VED03JL-5 K12**


Valve Bolts: 4 SHC screws 10-24 NC x 1.25" ASTM A574
Torque: 4-6 lb.-ft. (5.4 - 8 Nm)
Threads of mounting holes: 10-24 NC

1	Mounting surface with sealing rings: QTY 4 O-Ring size AS568-012 / 90 Shore
2	Coil removal space
3	Manual override by pin integrated in the solenoid tube
4	Connection M12 A 5 pin
5	L1 LED
6	L2 LED
7	Mating connector M12 5 poles - code A, female. To be ordered separately.
8	Adjustment sealing performed at factory. Do not disassemble the transducer.

VED03 J Series

IDENTIFICATION CODE: Standard (7 Pin) Electronics

VED03MJ - - - - - **D** - _____ DESIGN LETTER

Proportional D03 Direct Operated
with Digital On-Board Controls
Standard 7 PIN Connection

FUNCTION	
3	<p>Dual Solenoid 3 Position Spring Centered</p>
5	<p>Single Solenoid 2 Position Spring Centered</p>
10	<p>Dual Solenoid 4 Position with Fail-Safe Feature - Spring Centered (Code ZC Spools only)</p>

SEALS	
CODE	DESCRIPTION
A	BUNA (STD)
G	VITON

REFERENCE SIGNAL	
CODE	DESCRIPTION
E0	Voltage \pm 10 V (STD)
E1	Current 4-20 mA

NOMINAL CONTROLLED FLOW with ΔP 10 Bar P-T	
CODE	FLOW RATE
01	1 l/min
04	4 l/min
12	12 l/min
18	18 l/min (AC spool only)
30	30 l/min
30/15	30 (P-A) / 15 (P-B) l/min

CONNECTION	
CODE	DESCRIPTION
OBW	On board electronics - Internal Enable monitor signal PIN F to PIN B
OBC	On board electronics - PIN C Enable monitor signal PIN F to PIN B
OBM	On board electronics - Internal Enable monitor signal PIN F to PIN C

SPOOLS				
NAME	SYMBOLS	DESCRIPTION	APPLICATION	FUNCTION MATCHING
AC		METER IN / METER OUT	MOTION CONTROL	3, 5
FC				
ZC				
ZCF		METER IN / METER OUT WITH FAIL SAFE		10

Note: Function Code 5 valve only available with solenoid supplied on A port end. (P-B / A-T)

TYPICAL ORDERING CODE:
VSD03MJ-3AC-30-A-OBWE0D-*

VED03 J Series

VED03MJ ELECTRONICS COMMON DATA

Duty cycle		100% (continuous operation)
Protection class according to EN 60529		IP65 / IP67
Supply voltage	V DC	24 (from 19 to 30 VDC), ripple max 3 Vpp
Power consumption	VA	25
Maximum solenoid current	A	1.88
Fuse protection, external	A	3
Managed breakdowns		Overload and electronics overheating, LVDT sensor error, cable breakdown, supply voltage failure
Electromagnetic compatibility (EMC) emissions EN 61000-6-4, immunity EN 61000-6-2		According to 2014/30/EU standards


VED03MJ - STANDARD ELECTRONICS

3.1 - Electrical characteristics


Command signal: voltage (E0) current (E1)	V DC mA	±10 (Impedance Ri = 11 kOhm) 4 - 20 (Impedance Ri = 58 Ohm)
Monitor signal: voltage (E0) current (E1)	V DC mA	0 - 5 (Impedance Ro > 1 kOhm) 4 - 20 (Impedance Ro = 500 Ohm)
IO-Link communication (IOL): Data rate	kBaud	IO-Link Port Class B 230.4
Can Open communication (CA): Data rate	kbit	10 - 1000
Data register (IOL and CA versions only)		Solenoid voltage supply, solenoid faults (short circuit, bad config, internal), box temperature, switch-on time, vibrations
Connection		5-pin M12 code A (IEC 61076-2-101)

On-board electronics diagrams


VERSION OBC - External Enable



VERSION OBW - Internal Enable





VERSION OBM - 0V Monitor



VED03 J Series

VED03MJ Versions with voltage command (E0)



The reference signal is between -10V and +10V on double solenoid valve, and 0 - 10V on single solenoid valve.
 The monitor feature of versions OBW and OBM becomes available with a delay of 0.5 sec from the power-on of the card.



VDD03MJ Versions with current command (E1)




The reference signal is supplied in current 4 - 20 mA. If the current for command is lower, the card shows a breakdown cable error. To reset the error is sufficient to restore the signal.

The monitor feature of versions OBW and OBM becomes available with a delay of 0.5 sec from the power-on of the card.



VED03 J Series
VED03MJ - OVERALL AND MOUNTING DIMENSIONS

Dimensions inch (mm)

VED03MJ-3**

VED03MJ-5**


Valve Bolts: 4 SHC screws 10-24 NC x 1.25" ASTM A574
Torque: 4-6 lb.-ft. (5.4 - 8 Nm)
Threads of mounting holes: 10-24 NC

1	Mounting surface with sealing rings: QTY 4 O-Ring Size AS568-012 / 90 Shore
2	Coil removal space (solenoid B only)
3	Main connection 6 pin + PE
4	Mating connector 6 poles + PE, female type MIL-5015-G To be ordered separately.
5	Adjustment sealing performed at factory. Do not disassemble the transducer.

VED03 J Series

IDENTIFICATION CODE: Fieldbus Electronics

VED03JH - - - - - **K16** - ——— DESIGN LETTER

Proportional D03 Direct Operated Control with Digital On-Board and Fieldbus Controls

FUNCTION	
3	<p style="text-align: center;">Dual Solenoid 3 Position Spring Centered</p>
5	<p style="text-align: center;">Single Solenoid 2 Position Spring Centered</p>
10	<p style="text-align: center;">Dual Solenoid 4 Position with Fail-Safe Feature - Spring Centered (Code ZC Spools only)</p>

SEALS	
CODE	DESCRIPTION
A	BUNA (STD)
G	VITON

NOMINAL CONTROLLED FLOW with ΔP 10 Bar P-T	
CODE	FLOW RATE
01	1 l/min
04	4 l/min
12	12 l/min
18	18 l/min (AC spool only)
30	30 l/min
30/15	30 (P-A) / 15 (P-B) l/min

CONNECTIONS (Select one for each X connection)		
	CODE	DESCRIPTION
X1 Main Connector Configuration (Select One)	D1	One Command
	D0	Full Digital (on request - available for reference signal FD type Only)
X2, X3 Fieldbus type (Select One)	CA	CAN Open
	PD	PROFIBUS DP
	EC	EtherCAT
	EN	Ethernet / IP
	PN	Profinet
X7 Digital Transducer (Select One)	0	None
	1	SSI Type
	2	Encoder Type
X4 Analog transducer (Select One)	0	None
	1	Single / Double Transducer

SPOOLS				
NAME	SYMBOLS	DESCRIPTION	APPLICATION	FUNCTION MATCHING
AC		METER IN / METER OUT	MOTION CONTROL	3, 5
FC				
ZC				
ZCF		METER IN / METER OUT WITH FAIL SAFE		10

CONTROL INTERFACE	
CODE	DESCRIPTION
E0	Analog Voltage (±10V)
E1	Analog current (4-20MA)
FD	Full Digital Version (on Request)

Note: Function Code 5 valve only available with solenoid supplied on A port end. (P-B / A-T)

TYPICAL ORDERING CODE:
VSD03JH-3AC-30-A-E0K16DIEN00

VED03 J Series

VED03JH - FIELDBUS ELECTRONICS

The 11+ PE pin connection allows separate supply voltage for electronics and solenoids.



VED03JH Electrical characteristics

Command signal: voltage (E0) current (E1) digital (FD)	V DC mA	±10 (Impedance Ri = 11 kOhm) 4 - 20 (Impedance Ri = 58 Ohm) via fieldbus
Monitor signal: voltage (E0) current (E1)	V DC mA	±10 (Impedance Ro > 1 kOhm) 4 - 20 (Impedance Ro = 500 Ohm)
Communication / diagnostic		via Bus register
Communication interface standards CAN Open PROFIBUS DP EtherCAT, Ethernet /IP, Profinet, PowerLink		EN 50325-4 + DS408 EN 50170-2 / IEC 61158 IEC 61158
Communication physical layer CAN Open PROFIBUS DP EtherCAT, Ethernet /IP, Profinet, PowerLink		optical insulated CAN ISO 11898 optical insulated RS485 fast ethernet, insulated 100 Base TX
Power connection		11 pin + PE (DIN 43651)



COMMAND	-10V	0V	+10v	4 mA	12 mA	20 mA
MONITOR	-10V	0V	+10v	4 mA	12 mA	20 mA

X1 Main connection pin table



D1: one command


Pin	Values	Function
1	24V DC	Main supply voltage
2	0V	
3	24V DC	Enable
4	± 10V (E0) 4 - 20 (E1)	Command
5	0V	Command reference signal
6	± 10V (E0) 4 - 20 (E1)	Monitor (0V reference pin 10)
7	NC	do not connect
8	NC	do not connect
9	24V DC	Logic and control supply
10	0V	
11	24V DC	Fault (0V DC) or normal working (24V DC) (0V reference pin 2)
12	GND	Ground (Earth)

D0: full digital


Pin	Values	Function
1	24V DC	Main supply voltage
2	0V	
3	24V DC	Enable
4	NC	do not connect
5	NC	do not connect
6	NC	do not connect
7	NC	do not connect
8	NC	do not connect
9	24V DC	Logic and control supply
10	0V	
11	24V DC	Fault (0V DC) or normal working (24V DC) (0V reference pin 2)
12	GND	Ground (Earth)

VED03 J Series
VED03JH FIELDBUS connections


Please wire following guidelines provided by the relative standards communication protocol.

Communication connection CA (CAN Open)
X2 (IN) connection: M12 A 5 pin female


Pin	Values	Function
1	CAN_SH	Shield
2	NC	Do not connect
3	GND	Signal zero data line
4	CAN_H	Bus line (high)
5	CAN_L	Bus line (low)

X3 (OUT) connection: M12 A 5 pin male



Pin	Values	Function
1	CAN_SH	Shield
2	NC	Do not connect
3	GND	Signal zero data line
4	CAN_H	Bus line (high)
5	CAN_L	Bus line (low)

Communication connection PD (PROFIBUS DP)
X2 (IN) connection: M12 B 5 pin male (IN)



Pin	Values	Function
1	+5 V	Termination supply signal
2	PB_A	Bus line (high)
3	0 V	Data line and termination signal 0
4	PB_B	Bus line (low)
5	SHIELD	

X3 (OUT) connection: M12 B 5 pin female


Pin	Values	Function
1	+5 V	Termination supply signal
2	PB_A	Bus line (high)
3	0 V	Data line and termination signal 0
4	PB_B	Bus line (low)
5	SHIELD	

Communication connections: EC (EtherCat), EN (Ethernet/IP), PN (PROFINET), PL (POWERLINK)
X2 (IN) connection M12 D 4 pin female


Pin	Values	Function
1	TX+	Transmitter
2	RX+	Receiver
3	TX-	Transmitter
4	RX-	Receiver
HOUSING	shield	

X3 (OUT) connection: M12 D 4 pin female


Pin	Values	Function
1	TX+	Transmitter
2	RX+	Receiver
3	TX-	Transmitter
4	RX-	Receiver
HOUSING	shield	



Note: Shield connection on connector housing is recommended.

VED03 J Series

Digital transducer connection



X7 connection: M12 A 8 pin female)

VERSION 1: SSI type



Pin	SSI Values	Function	Notes
1	CLK+	Serial synchronous clock (+)	Input - digital signal
2	CLK-	Serial synchronous clock (-)	
3	MISO+	Serial position data (+)	
4	MISO-	Serial position data (-)	
5	NC	-	do not connect
6	NC	-	
7	+24 V	transducer power supply	Output power supply
8	0 V	-	Common GND


VERSION 2: ENCODER type



Pin	SSI Values	Function	Notes
1	ENC_Z+	input channel Z+	Input - digital signal
2	ENC_Z-	input channel Z-	
3	ENC_A+	input channel A+	
4	ENC_A-	input channel A-	
5	ENC_B+	input channel B+	
6	ENC_B-	input channel B-	
7	+5 V	transducer power supply	Output power supply
8	0 V	-	Common GND

Analogue transducer connection X4 connection: M12 A 4 pin female

VERSION 1: single / double transducer (single or double is a software-selectable option)




Pin	Values	Notes
1	+24V	Remote transducer power supply (out) 100 mA
2	±10 V 4 ±20 mA	Input signal of transducer 1 (range software selectable)
3	0V	Common reference signal for transducer power and signals
4	±10 V 4 ±20 mA	Input signal of transducer 2 (range software selectable)
5	-	

VED03 J Series

VED03JH - OVERALL AND MOUNTING DIMENSIONS


Dimensions inch (mm)

VED03JH-3**



Note: Depending on the chosen version, X4 and X7 connections may not be present. Please refer to page 10-12 for connection descriptions and pinout.

VED03JH-5**



Valve Bolts: 4 SHC screws 10-24 NC x 1.25" ASTM A574
Torque: 4-6 lb.-ft. (5.4 - 8 Nm)
Threads of mounting holes: 10-24 NC

X1	Main connection 11 pin + PE
X2	Fieldbus communication (IN)
X3	Fieldbus communication (OUT)
X4	X4 connection for analogue transducer
X7	X7 connection for digital transducer






1	Mounting surface with sealing rings: QTY 4 O-Ring AS568-012 / 90 Shore
2	Coil removal space (solenoid B only)
3	Manual override by pin integrated in the solenoid tube
4	Mating connector 11 poles + PE To be ordered separately.
5	Mating connectors for fieldbus communication and signals To be ordered separately.

VED03 J Series

VED03 J Series - CHARACTERISTIC CURVES

(obtained with mineral oil with viscosity of 36 cSt at 50°C and with digital integrated electronics)

Typical flow rate curves related to the reference signal and measured for the available spools.
The Δp values are measured between P and T valve ports.



Common Conversions Formulas:






LPM to GPM (LPM x .2642 = GPM)

GPM to LPM (GPM x 3.785 = LPM)


Bar to PSI (Bar x 14.5 = PSI)

PSI to Bar (PSI x .06895 = Bar)

VED03 J Series



VED03 J Series



Flow P→B / A→T with valve in fail safe position, depending on the inlet pressure.



When a power failure (enabling OFF) occurs, the valve moves in 'fail safe' position, maintaining a minimum flow that allows the actuator to return slowly to a safe position.

During the black-out the centering springs retain the spool in fail safe-position.


RESPONSE TIMES

(obtained with mineral oil with viscosity of 36 cSt at 50°C and 140 bar Δp P→T)

FREQUENCY RESPONSE (ZC SPOOLS)



Z SPOOLS - PRESSURE GAIN



The diagram shows the valve pressure gain, expressed as % of the ratio between the port pressure variation in A or B (Δp AB) and the P system pressure, according to the reference signal.

In practice, the pressure gain states the valve reaction towards external disturbances aimed at changing the actuator position.

ACCESSORIES CATALOGS

CONTINENTAL VALVE ACCESSORIES
Connectors and Cable Sets

Connectors and Cable Sets

Standard Directional Control Valves

Male Receptacles

VEA-3C-A
(5 PIN)
1001849

VEA-3MH-A
(5 PIN)
1001849

VEA-3L4-A
(4 PIN)
1001850

Female Receptacles

VEA-3M-A
(5 PIN)
764051
6 ft. cord

VEA-3L-A
(4 PIN)
764054
6 ft. cord

DIN Connector
43550 Form A / ISO 4400

VEA-3E-A (6-pin)
165639

VEA-3E-R (6-pin)
165639

Cable Glands
VSD-HL-HDZ

PC11 ISO
Strain Relief

VEA-DT06-CS-A
(6 PIN)
1021690C
(Deutsch)

Table:

Ordering	Accessories
1021690C	VEA-DT06-CS-A 6-pin Deutsch
1021690C	VEA-DT06-CS-A 6-pin Deutsch (with strain relief)
1021690C	VEA-DT06-CS-A 6-pin Deutsch (with strain relief and PC11 ISO)
1021690C	VEA-DT06-CS-A 6-pin Deutsch (with strain relief and PC11 ISO)

www.continentalhydraulics.com - sales@conthyd.com 1027453 Rev 01/22 1/5

CONTINENTAL VALVE ACCESSORIES
Programming and Test Devices

Programming and Test Devices

For **IO-Link** and Proportional Valves with Integrated Electronics

OPERATING PRINCIPLE

The kit contains a test device with embedded cable to connect to the valve. A USB cable for PC connection and a power adapter. The dedicated software is available for download from our website.

The device is suitable for troubleshooting and functional testing of Continental's proportional valves for open loop (type G, GH) and closed loop (type J, JH, JH1, JH2) valves and IO-Link or IO-Link valves (type J, JH, JH1, JH2).

The software allows to check settings, diagnostics and errors to verify the desired parameter settings made in reality, adapting it to your system.

No additional power supply is required; the device uses the supply source coming from the system cable.

TECHNICAL CHARACTERISTICS

Power supply	VDC	24 (18 + 30)
Current consumption	mA	50
Valve side connection:	VEA-PB1 VEA-PB2	6 pins M12 11 pins M12 (2x4 + 4x5)
PC side connection	VEA-PB12	11 pins M12 (2x4 + 4x5)
PC side connection	USB 2.0 cable	
Electromagnetic compatibility (EMC)		according to 2014/53/EU EN 61000-6-4 (immunity) EN 61000-6-2 (emissions)
Housing dimensions	mm	104x84x41 + 2000 (output cable)
Operating temperature range	°C	-20 + 60
Protection degree		IP 20

IDENTIFICATION CODE

VEA-PB + [] + []

Ordering information: For the identification code, see the identification code table.

For ordering type:

1	VEA-PB1 (6-pin)
2	VEA-PB2 (11-pin)
3	VEA-PB12 (11-pin)

www.continentalhydraulics.com - sales@conthyd.com 1027454 Rev 01/22 1/4

Connectors and Cables Sets
Form #1027453

Programming and Test Devices
Form #1027454